

# AL-F High Performance Grease



## Available sizes:

|          |                                      |
|----------|--------------------------------------|
| 26550035 | AL-F High Performance Grease 350 g   |
| 26550040 | AL-F High Performance Grease 400 g   |
| 26550100 | AL-F High Performance Grease 1.0 kg  |
| 26550500 | AL-F High Performance Grease 5.0 kg  |
| 26550925 | AL-F High Performance Grease 25.0 kg |

## Accessories:

|          |                           |
|----------|---------------------------|
| 10953001 | Processing Spatula, short |
| 10953003 | Processing Spatula, long  |

## Allround High Performance Grease NSF approval

WEICON AL-F can be used to lubricate rolling and sliding bearings, joints, levers, sliding guides, spindles, spline shafts, camshafts, open gears, worm gears and all grease lubrication points, even in the food industry.



## Technical Data

|                                    |  |
|------------------------------------|--|
| Abbreviation (DIN 51502)           | KLF 2K -30                             |
| Consistency assignment (DIN 51818) | NLGI-Class 2                           |
| Composition                        | Lithium soap / mineral oil             |
| Colour                             | white                                  |
| Conforms to                        | NSF-H 2, LFGB Section 31 and Section 5 |
| Temperature resistance             | -30 to +120 °C                         |
| ISSA-Code                          | 53.052.30/31                           |

## Surface pre-treatment

Clean surfaces.

## Processing

Apply AL-F evenly.

## Storage

Keep in closed original container. Do not store together with oxidizing agents. Keep container tightly closed and store at cool and ventilated place. Recommended storage temperature: room temperature.

## Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets ([www.weicon.com](http://www.weicon.com)) must be observed.

## Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG  
(Headquarters)  
Germany  
phone +49 (0) 251 9322 0  
info@weicon.de

WEICON Middle East L.L.C.  
United Arab Emirates  
phone +971 4 880 25 05  
info@weicon.ae

WEICON Inc.  
Canada  
phone +1 877 620 8889  
info@weicon.ca  
www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.  
Turkey  
phone +90 (0) 212 465 33 65  
info@weicon.com.tr  
www.weicon.com.tr

WEICON Romania SRL  
Romania  
phone +40 (0) 3 65 730 763  
office@weicon.com

WEICON SA (Pty) Ltd  
South Africa  
phone +27 (0) 21 709 0088  
info@weicon.co.za

WEICON South East Asia Pte Ltd  
Singapore  
phone (+65) 6710 7671  
info@weicon.com.sg

WEICON Czech Republic s.r.o.  
Czech Republic  
phone +42 (0) 417 533 013  
info@weiconcz.cz

WEICON Ibérica S.L.  
Spain  
phone +34 (0) 914 7997 34  
info@weicon.es