

Adhesive Spray for detachable joints



transparent

WEICON Adhesive Spray for detachable joints is especially suited for detachable and adjustable joints. It is colourless, does not soak through or cause discolouration, and does not leave a wavy surface, even when used on thin materials. Adhesive Spray for detachable joints can be used to bond paper, cardboard and foils to themselves and among each other. The joint is detachable when the spray is applied to one side; applying the spray to both sides makes the joint permanent.

WEICON Adhesive Spray for detachable joints can be used, for example, to fuse templates, billboards, posters, photos, decorations in trade show construction, layouts and technical drawings.

Technical Data

Base	synthetic rubber
Processing temperature	+10 to +30 °C
Evaporation time	5 - 15 min.
Open time max.	45 min.
Effectiveness	13 m ²
Temperature resistance	-20 to +65 °C
Storage stability	12 months

Processing

1. Shake can before use. Surfaces must be dry, clean and free of grease. Spray onto the surface at about 15 to 30 cm distance. Detachable if a thin adhesive layer is applied on only one surface. For permanent adhesion, Adhesive Spray should be applied either

in a thick layer or on both surfaces. 2. Depending on surface characteristics and ambient temperature, let the spray film dry (about 10 minutes) until the adhesive is no longer stringy. 3. Position the parts and join them with strong pressure

Storage

Pressurized container: protect from sunlight and do not expose to temperatures exceeding +50°C.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

11802500 Adhesive Spray for detachable joints 500 ml

Accessories:

11202400 Sealant and Adhesive Remover, 400 ml
 11207400 Surface Cleaner, 400 ml
 11850200 Hand Protective Foam, 200 ml

Note

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG
 (Headquarters)
 Germany
 phone +49 (0) 251 9322 0
 info@weicon.de

WEICON Middle East L.L.C.
 United Arab Emirates
 phone +971 4 880 25 05
 info@weicon.ae

WEICON Inc.
 Canada
 phone +1 877 620 8889
 info@weicon.ca
 www.weicon.ca

WEICON Kimya Sanayi Tic. Ltd. Şti.
 Turkey
 phone +90 (0) 212 465 33 65
 info@weicon.com.tr
 www.weicon.com.tr

WEICON Romania SRL
 Romania
 phone +40 (0) 3 65 730 763
 office@weicon.com

WEICON SA (Pty) Ltd
 South Africa
 phone +27 (0) 21 709 0088
 info@weicon.co.za

WEICON South East Asia Pte Ltd
 Singapore
 phone (+65) 6710 7671
 info@weicon.com.sg

WEICON Czech Republic s.r.o.
 Czech Republic
 phone +42 (0) 417 533 013
 info@weiconcz.cz

WEICON Ibérica S.L.
 Spain
 phone +34 (0) 914 7997 34
 info@weicon.es