

WEICON Pipe Repair Kit



The set is designed for the emergency repair of defective and damaged pipes and pipelines.

It comprises one WEICON Repair Stick Steel, a special repair tape made of fibreglass-reinforced plastic, assembly instructions and a pair of protective gloves.

The repair tape is impregnated with a special resin and activated by contact with water.

The Pipe Repair Kit can be processed without any additional tools and is used for the reliable and permanent sealing of cracks and leaks. It is very easy and quick to use and shows excellent adhesive properties, high pressure and chemical resistance as well as temperature resistance up to 150°C. Within 30 minutes, the tape is fully cured and hard-wearing.

Due to the fabric properties of the tape, the resulting high flexibility and the simple processing, the repair kit is particularly suitable for sealing leaks in bends, T-pieces or in spaces difficult to access.

It can be used on many different surfaces such as stainless steel, aluminium, copper, PVC, many plastics, fibreglass, concrete, ceramics and rubber.



Technical Data

Epoxy resin steel-filled pasty
pasty
dark-grey
1:1
2,0 g/cm ³
15 mm
+10 to +35 °C

Curing temperature	+6 to +40 °C
Polt life for 25gr preparation and +20°C (+68°F)	4 min.
Handling strength (35% strength) after	10 min.
Capable of bearing mechanical loads (50% strength)	after 60 min.
Final strength (100%) after	24 h
Pressure (DIN 53281-83)	80 N/mm²
Medium shear strength after 7 days at +20°C (+65°F) DIN EN 1465 at	Steel sandblasted: 4,1 N/mm²
Shore hardness D	75
Thermal conductivity (ASTM D 257)	0,6 W/m·K
Linear shrinkage	<1 %
Electrical resistance (ASTM D 149)	5•10 ¹¹ Ohm/cm
Dielectric strength (ASTM D 149)	3,0 kV/mm
Thermal expansion coefficient (ISO 11359)	30-40 x 10^-6 K^-1
Temperature resistance	-50 to +120 briefly +150 °C
Technical Data Repair Tape	
Pot-life at +20°C (+68°F)	3 - 5 min.
Handling strength (35% strength) after	7 - 10 min.
Final hardness after	30 min.
Tensile strength	35 N/mm²
Compressive strength	150 bar
Shore D (ATSM D 1706)	70
Temperature resistance	to +150 °C

Information about surface pre-treatment and processing can be found in the manual.

Storage

Store WEICON Pipe Repair Kit at room temperature (but up to max. +25°C) in a dry place. Unopened containers can be stored for 24 months at temperatures from +18 to +25°C.

Safety and health

When using WEICON products, the physical, safety technical, toxicological and ecological data and regulations in our EC safety data sheets (www.weicon.com) must be observed.

Available sizes:

10710001	WEICON Pipe Repair Kit 5 cm x 1,5 m
10710002	WEICON Pipe Repair Kit 5 cm x 3,6 m
10710003	WEICON Pipe Repair Kit 10 cm x 3,6 m

The specifications and recommendations given in this technical data sheet must not be seen as guaranteed product characteristics. They are based on our laboratory tests and on practical experience. Since individual application conditions are beyond our knowledge, control and responsibility, this information is provided without any obligation. We do guarantee the continuously high quality of our products. However, own adequate laboratory and practical tests to find out if the product in question meets the requested properties are recommended. A claim cannot be derived from them. The user bears the only responsibility for non-appropriate or other than specified applications.

WEICON GmbH & Co. KG Germany phone +49 (0) 251 9322 0

info@weicon.de

WEICON SA (Pty) Ltd South Africa phone +27 (0) 21 709 0088 info@weicon.co.za

United Arab Emirates phone +971 4 880 25 05

WEICON South East Asia Pte Ltd Singapore phone (+65) 6710 7671

Canada phone +1 877 620 8889 www.weicon.ca

WEICON Czech Republic s.r.o. Czech Republic phone +42 (0) 417 533 013

WEICON Kimya Sanayi Tic. Ltd. Şti. Turkey phone +90 (0) 212 465 33 65 www.weicon.com.tr

WEICON Ibérica S.L. Spain phone +34 (0) 914 7997 34 www.weicon.es

WEICON Romania SRL Romania phone +40 (0) 3 65 730 763 office@weicon.com www.weicon.com.ro

WEICON Italia S.r.I. phone (+39) 0102924871 www.weicon.it